

COONABARABRAN

RWY	(CN)	TORA	TODA	ASDA	LDA
01	(1)	649 (2129)	709 (2326) (2.34%)	649 (2129)	649 (2129)
		RESA dimensions 60M X 150M commences from RWS end.			
19	(1)	649 (2129)	709 (2326) (1.2%)	649 (2129)	649 (2129)
		RESA dimensions 60M X 90M commences from RWY end.			
		Slope 0.2% DOWN to S. RWY WID 60 RWS WID 90 Graded 60			
11	(3)	1520 (4987)	1671 (5482) (3.45%)	1611 (5285)	1520 (4987)
		RESA dimensions 90M X 90M commences from RWY end.			
29	(3)	1520 (4987)	1610 (5282) (3.76%)	1520 (4987)	1520 (4987)
		RESA dimensions 90M X 90M commences from SWY end.			

1. CAUTION: OBST fences 6FT high and PARL to RWY, 73M N and S of RCL are not taken into account in the calculation of TODA GRAD and STODA.

Slope 0.2% down to E for W 600(1969) 0.3% down to W for remainder. RWY WID 30 RWS WID 150 Graded 90

SUPPLEMENTARY TAKEOFF DISTANCES

RWY11- 1647(5403)(1.6) 1654(5426)(1.9) 1659(5443)(2.2) 1663(5456)(2.5) 1670(5479)(3.3)
 RWY29- 1035(3396)(1.9) 1452(4764)(2.2) 1501(4924)(2.5) 1583(5194)(3.3)