

MELBOURNE/ESSENDON

RWY	(CN)	TORA	TODA	ASDA	LDA
08	(4)	1921 (6302)	1981 (6499) (3.16%)	1921 (6302)	1921 (6302)
RESA dimensions 60M X 90M commences from RWY end.					
26	(4)	1921 (6302)	1981 (6499) (4.02%)	1921 (6302)	1921 (6302)
RESA dimensions 60M X 90M commences from RWY end.					
1. OBST in flyover area of RWS refer ERSA.					
2. Multiple lit and unlit masts BTN 2061-2204M FM RWY 26 SOT BTN 101M L and 101M R RCL.					
3. Masts infringe 2% TKOF SFC up to 3.3% not ABV 261FT AMSL.					
4. Masts are street lights along the Tullamarine Freeway.					
Slope 0.4% down to the W for 700M then 0.2% down to E for the remainder. RWY WID 45					
RWS WID 180 Graded 150					
17	(3)	1503 (4931)	1563 (5128) (2.73%)	1503 (4931)	1503 (4931)
RESA dimensions 60M X 90M commences from RWY end.					
35	(3)	1503 (4931)	1563 (5128) (1.82%)	1503 (4931)	1503 (4931)
RESA dimensions 60M X 90M commences from RWY end.					
RWY 35 fixed distance and touch down zone markings displaced 33M to N.					
Slope 0.9% down to S. RWY WID 45 RWS WID 150					

SUPPLEMENTARY TAKEOFF DISTANCES

RWY08- 1904(6247)(1.6) 1936(6352)(1.9) 1954(6411)(2.2) 1964(6443)(2.5)
RWY26- 1690(5545)(1.6) 1765(5791)(1.9) 1821(5974)(2.2) 1864(6115)(2.5) 1933(6342)(3.3)
RWY17- 1419(4655)(1.6) 1463(4800)(1.9) 1499(4918)(2.2) 1538(5046)(2.5)
RWY35- 1302(4272)(1.6)