

**MELBOURNE/ESSENDON**

<b>RWY</b>	<b>(CN)</b>	<b>TORA</b>	<b>TODA</b>	<b>ASDA</b>	<b>LDA</b>
08	(4)	1921 (6302)	1981 (6499) (2.28%)	1921 (6302)	1921 (6302)
RESA dimensions 60M X 90M commences from RWY end.					
26	(4)	1921 (6302)	1981 (6499) (3.87%)	1921 (6302)	1921 (6302)
RESA dimensions 60M X 90M commences from RWY end.					
1. OBST in flyover area of RWS refer ERSA.					
2. Multiple lit and unlit masts BTN 2061-2204M FM RWY 26 SOT BTN 101M L and 101M R RCL.					
3. Masts infringe 2% TKOF SFC up to 3.3% not ABV 261FT AMSL.					
4. Masts are street lights along the Tullamarine Freeway.					
Slope 0.4% down to the W for 700M then 0.2% down to E for the remainder. RWY WID 45 RWS WID 180 Graded 150					
17	(3)	1503 (4931)	1563 (5128) (2.78%)	1503 (4931)	1503 (4931)
RESA dimensions 60M X 90M commences from RWY end.					
35	(3)	1503 (4931)	1563 (5128) (1.82%)	1503 (4931)	1503 (4931)
RESA dimensions 60M X 90M commences from RWY end.					
RWY 35 fixed distance and touch down zone markings displaced 33M to N.					
Slope 0.9% down to S. RWY WID 45 RWS WID 150					

**SUPPLEMENTARY TAKEOFF DISTANCES**

RWY08-	1918(6293)(1.6)	1949(6394)(1.9)	1973(6473)(2.2)		
RWY26-	1740(5709)(1.6)	1798(5899)(1.9)	1839(6033)(2.2)	1873(6145)(2.5)	1942(6371)(3.3)
RWY17-	1414(4639)(1.6)	1459(4787)(1.9)	1494(4902)(2.2)	1533(5029)(2.5)	
RWY35-	1302(4272)(1.6)				