MELBOURNE/ESSENDON

RWY	(CN)	TORA	TODA	ASDA	LDA
08	(4)	1921 (6302)	1981 (6499) (2.28%)	1921 (6302)	1921 (6302)

RESA dimensions 60M X 90M commences from RWY end.

26	(4)	1921 (6302)	1981 (6499) (3.87%)	1921 (6302)	1921 (6302)

RESA dimensions 60M X 90M commences from RWY end.

1. OBST in flyover area of RWS refer ERSA.

2. Multiple lit and unlit masts BTN 2061-2204M FM RWY 26 SOT BTN 101M L and 101M R RCL.

3. Masts infringe 2% TKOF SFC up to 3.3% not ABV 261FT AMSL.

4. Masts are street lights along the Tullamarine Freeway.

Slope 0.4% down to the W for 700M then 0.2% down to E for the remainder. RWY WID 45 RWS WID 180 Graded 150

17	(3)	1503 (4931)	1563 (5128) (2.78%)	1503 (4931)	1503 (4931)

RESA dimensions 60M X 90M commences from RWY end.

35	(3)	1503 (4931)	1563 (5128) (1.82%)	1503 (4931)	1503 (4931)

RESA dimensions 60M X 90M commences from RWY end.

RWY 35 fixed distance and touch down zone markings displaced 33M to N.

Slope 0.9% down to S. RWY WID 45 RWS WID 150

SUPPLEMENTARY TAKEOFF DISTANCES

RWY08- 1918(6293)(1.6) 1949(6394)(1.9) 1973(6473)(2.2)
RWY26- 1740(5709)(1.6) 1798(5899)(1.9) 1839(6033)(2.2) 1873(6145)(2.5) 1942(6371)(3.3)
RWY17- 1414(4639)(1.6) 1459(4787)(1.9) 1494(4902)(2.2) 1533(5029)(2.5)
RWY35- 1302(4272)(1.6)