

MERIMBULA

RWY	(CN)	TORA	TODA	ASDA	LDA
03	(3)	1602 (5256)	1662 (5453) (3.58%)	1602 (5256)	1602 (5256)
RESA dimensions 90M X 60M commences from RWY end.					
Fence 7.9FT ABV and PARL to RWY, 81M E of RCL, and transient OBST up to 13.4FT ABV and 95M NE of RWS end, not taken into account in the calculation of TODA GRAD and STODA.					
Use of alternate start position RWY 03 PPR.					
RWY 03 ALTERNATE declared distances:					
TORA		TODA	ASDA	LDA	
1721		1781(3.58)	1721	1602	
SUPPLEMENTARY TAKEOFF DISTANCES					
1010(2.2)		1350(2.5)	1764(3.3)		
21	(3)	1602 (5256)	1662 (5453) (3.51%)	1602 (5256)	1602 (5256)
RESA dimensions 90M X 60M commences from RWY end.					
TKOF climb SFC inner edge 150M. Transition SFC infringed by trees both sides of RWY.					
Use of alternate start position RWY 21 PPR.					
RWY 21 ALTERNATE declared distances:					
TORA		TODA	ASDA	LDA	
1721		1781(3.51)	1721	1602	
SUPPLEMENTARY TAKEOFF DISTANCES					
1679(3.3)					
Slope Level. RWY WID 30 RWS WID 90					
SUPPLEMENTARY TAKEOFF DISTANCES					
RWY03-	891(2923)(2.2)	1231(4039)(2.5)	1645(5397)(3.3)		
RWY21-	1560(5118)(3.3)				