

MERIMBULA

RWY	(CN)	TORA	TODA	ASDA	LDA
03	(3)	1602 (5256)	1662 (5453) (3.47%)	1602 (5256)	1602 (5256)

Fence 7.9FT ABV and PARL to RWY, 81M E of RCL, and transient OBST up to 13.4FT ABV and 95M NE of RWS end, not taken into account in the calculation of TODA GRAD and STODA.

Use of alternate start position RWY 03 PPR.

RWY 03 ALTERNATE declared distances:

TORA TODA ASDA LDA

1721 1781(3.47) 1721 1602

SUPPLEMENTARY TAKEOFF DISTANCES

1015(2.2) 1354(2.5) 1767(3.3)

21	(3)	1602 (5256)	1662 (5453) (3.47%)	1602 (5256)	1602 (5256)
----	-----	-------------	---------------------	-------------	-------------

TKOF climb SFC inner edge 150M. Transition SFC infringed by trees both sides of RWY.

Use of alternate start position RWY 21 PPR.

RWY 21 ALTERNATE declared distances:

TORA TODA ASDA LDA

1721 1781(3.47) 1721 1602

SUPPLEMENTARY TAKEOFF DISTANCES

1698(3.3)

Slope Level. RWY WID 30 RWS WID 90

SUPPLEMENTARY TAKEOFF DISTANCES

RWY03- 896(2940)(2.2) 1235(4052)(2.5) 1648(5407)(3.3)

RWY21- 1579(5180)(3.3)