

DUBBO

RWY	(CN)	TORA	TODA	ASDA	LDA
05	(3)	1708 (5604)	1768 (5800) (1.62%)	1708 (5604)	1708 (5604)
RESA dimensions 60M X 45M commences from RWY end.					
23	(3)	1708 (5604)	1768 (5800) (2.7%)	1708 (5604)	1708 (5604)
RESA dimensions 60M X 45M commences from RWY end.					
Transient OBST up to 20.5FT ABV 199M SW of RWS end and fence 13.3FT ABV 186M SW of RWS end, not taken into account in the calculation of TODA GRAD and STODA.					
Slope 0.6% down to NE. Sealed blast areas 60 X 45 at RWY ends. RWY WID 45 RWS WID 150					
11	(2)	1067 (3501)	1127 (3697) (2.54%)	1067 (3501)	1067 (3501)
RESA dimensions 60M X 18M commences from RWY end.					
OBST: Fence 13FT ABV and up to 103M E of RWS end, not taken into account in the calculation of TODA GRAD and STODA.					
29	(2)	1067 (3501)	1127 (3697) (4.04%)	1067 (3501)	1067 (3501)
RESA dimensions 60M X 18M commences from RWY end.					
Slope 0.5% down to W. RWY WID 18 RWS WID 90					

SUPPLEMENTARY TAKEOFF DISTANCES

RWY05-	1765(5791)(1.6)				
RWY23-	1198(3930)(1.9)	1499(4918)(2.2)	1681(5515)(2.5)		
RWY11-	976(3202)(2.2)	1113(3652)(2.5)			
RWY29-	844(2769)(1.9)	911(2989)(2.2)	963(3159)(2.5)	1065(3494)(3.3)	