

TENNANT CREEK

RWY	(CN)	TORA	TODA	ASDA	LDA
07	(3)	1959 (6427)	2019 (6624) (2.81%)	1959 (6427)	1959 (6427)
RESA dimensions 120M X 90M commences from RWS end.					
25	(3)	1959 (6427)	2019 (6624) (2%)	1959 (6427)	1959 (6427)
RESA dimensions 110M X 90M commences from RWS end.					
OBST fences 6.3FT ABV, 98M south and 4.1FT ABV, 91M north, both PARL to RCL are not taken into account in determining TODA GRAD and STODA.					
Slope 0.4% down to W. RWY WID 30 RWS WID 150 Graded 90					
11	(2)	1054 (3458)	1114 (3655) (2.94%)	1054 (3458)	1054 (3458)
RESA dimensions 120M X 90M commences from RWS end.					
29	(2)	1054 (3458)	1178 (3865) (1.97%)	1054 (3458)	1054 (3458)
RESA dimensions 120M X 90M commences from RWS end.					
Slope 0.4% down to NW. RWY WID 23 RWS WID 90					

SUPPLEMENTARY TAKEOFF DISTANCES

RWY07-	1304(4278)(2.2)	1703(5587)(2.5)
RWY25-	1960(6430)(1.6)	2007(6585)(1.9)
RWY11-	806(2644)(2.2)	956(3136)(2.5)
RWY29-	1109(3638)(1.6)	1168(3832)(1.9)