

WARRNAMBOOL

| RWY | (CN) | TORA | TODA | ASDA | LDA |
|------------|-------------|---|---------------------|-------------|-------------|
| 04 | (2) | 1069 (3507) | 1129 (3704) (3.55%) | 1069 (3507) | 1069 (3507) |
| | | RESA dimensions 60M X 90M commences from RWS end. | | | |
| 22 | (2) | 1069 (3507) | 1129 (3704) (1.55%) | 1069 (3507) | 1069 (3507) |
| | | RESA dimensions 60M X 90M commences from RWS end. | | | |
| | | Slope 0.2% down to SW. RWY WID 23 RWS WID 90 | | | |
| 13 | (3) | 1372 (4501) | 1432 (4698) (6.27%) | 1372 (4501) | 1372 (4501) |
| | | RESA dimensions 80M X 90M commences from RWS end. | | | |
| | | Transient OBST 2.6FT ABV and 13.4M SE of RWS end not taken into account in the calculation of TODA, GRAD and STODA. | | | |
| 31 | (3) | 1372 (4501) | 1432 (4698) (3.63%) | 1372 (4501) | 1372 (4501) |
| | | RESA dimensions 80M X 90M commences from RWS end. | | | |
| | | 1. Approach transitional surface infringed by trees N side approximately 53M from RWS end. | | | |
| | | 2. Fence 4FT ABV and 16M NW of RWS end not taken into account in the calculation of TODA, GRAD and STODA. | | | |
| | | Slope 0.5% down to SE. RWY WID 30 RWS WID 150 Graded 90 | | | |

SUPPLEMENTARY TAKEOFF DISTANCES

| | | | | | |
|--------|-----------------|-----------------|-----------------|-----------------|-----------------|
| RWY04- | 927(3041)(1.9) | 1022(3353)(2.2) | 1051(3448)(2.5) | 1114(3655)(3.3) | |
| RWY13- | 1263(4144)(1.6) | 1293(4242)(1.9) | 1316(4318)(2.2) | 1334(4377)(2.5) | 1369(4491)(3.3) |
| | 1417(4649)(5.0) | | | | |
| RWY31- | 1028(3373)(1.9) | 1213(3980)(2.2) | 1324(4344)(2.5) | 1417(4649)(3.3) | |